



#### Selected Dimensions

##### Dimensions

A. LENGTH WITH BUCKET	9.5 ft in	2896 mm
B. WIDTH OVER TIRES	4 ft in	1226 mm
C. HEIGHT TO TOP OF CAB	5.9 ft in	1784 mm
D. WHEELBASE	2.9 ft in	874 mm
E. GROUND CLEARANCE	6 in	152 mm
F. LENGTH W/O BUCKET	7.3 ft in	2235 mm
G. CLEARANCE AT MAX LIFT AND DUMP	7 ft in	2146 mm
H. REACH AT MAX LIFT AND DUMP	22.8 in	578 mm

##### Specification

##### Engine

MAKE	Yanmar	
MODEL	3TNE88 diesel	
NET POWER	36 hp	26.8 kw
POWER MEASURED @	3000 rpm	
DISPLACEMENT	100 cu in	1.6 L

##### Operational

OPERATIONAL WEIGHT	4400 lb	1995.8 kg
FUEL CAPACITY	8.5 gal	32.2 L
HYDRAULIC SYSTEM FLUID CAPACITY	8 gal	30.3 L
MAX SPEED	6.8 mph	11 km/h
TIRE SIZE	8.50x15	
OPERATING VOLTAGE	12 V	
ALTERNATOR SUPPLIED AMPERAGE	40 amps	

##### Loader

OPERATING LOAD RATING	1050 lb	476.3 kg
-----------------------	---------	----------

##### Hydraulic

PUMP FLOW CAPACITY	14.4 gal/min	54.5 L/min
--------------------	--------------	------------

##### Dimensions

LENGTH WITH BUCKET	9.5 ft in	2896 mm
LENGTH W/O BUCKET	7.3 ft in	2235 mm
WIDTH OVER TIRES	4 ft in	1226 mm
HEIGHT TO TOP OF CAB	5.9 ft in	1784 mm
CLEARANCE AT MAX LIFT AND DUMP	7 ft in	2146 mm
WHEELBASE	2.9 ft in	874 mm
GROUND CLEARANCE	6 in	152 mm
REACH AT MAX LIFT AND DUMP	22.8 in	578 mm
TURNING RADIUS FROM CENTER - MACHINE REAR	26.5 in	672 mm
TURNING RADIUS FROM CENTER - INC BUCKET	34.4 in	872.5 mm

